



The **Ceiling Speaker** (CS-70V) has a tuned ported enclosure that provides superior bass response while maintaining efficiency. The speaker grill comes pre-installed from factory. An impedance selector switch is easily accessible under the removable grill. Spring-loaded mounting tabs make for easy and secure installation. All metal, spring-loaded terminals provide easy and convenient attachment of speaker wires. Metal speaker back meets UL 2043 criteria for plenum installation.



Speaker Specifications

Frequency Response	70 Hz to 15 kHz (-10dB) 100 Hz to 14 kHz +/- 2 dB
Power Handling	50 W continuous pink noise
Sensitivity	87 dB 1 Watt / 1 Meter
Impedance	Switchable 8 Ohms nominal 25V TAPS: 1.28, 0.64, 0.32, 0.16 Watts 75/100V TAPS: 10, 5, 2.5, 1.3 Watts
Type	Vented enclosure
Mounting	Spring-loaded mounting tabs
UL 2043	Speaker back can meets UL 2043 criteria for plenum installation
Weight	3 lbs. 6 oz. (1.53 kg)
Dimensions	Depth 5.8 in. (147.3 mm) Grill Diameter 8.5 in. (216.0 mm) Mounting hole 7.0 in. (178.0 mm)



Back can is RoHS and UL compliant.

