

CA-60A AMPLIFIER SPEC SHEET



The **CA-60A Amplifier** provides quality audio for teachers, students, and multimedia sources. This unit is equipped with an Eco Mode, which automatically reduces power consumption when no signal is present. It also features a PA voice override, so announcements can still be heard.

24V DC Power Input Speaker Output PA Mute Line Out Equalizer Line In XD Receiver Input WPA-03 Input



SPECIFICATIONS

ST-AM-9001 CA-60A SENTINEL AMPLIFIER WITH POWER SUPPLY	
Audio Power	50W
Power Requirements	24V DC Power
Connectors	(3) 3.5 mm TRS variable gain line inputs, (1) 3.5 mm TRS variable gain line output with front panel volume control, (1) 3.5 mm TRS connector for assistive listening devices, (1) 3.5 mm TRS rear panel line level out with level control, (1) RJ45 PoE input for XD Receiver
PA Connector	Connects to Public Address System and mutes amplifier during announcements
Accessory Port	Accepts WPA-03 Remote Wall Plate that provides an additional input with level control and ALD output with level control
Equalization	3-Band equalizer (Bass, Mid, Treble)
Weight	1.65 lbs (26.40 oz)
Dimensions	7.50 (H) x 4 (W) x 1.50 (D) in (190.50 x 101.60 x 38.10 mm)