




The **SAFE System Duress Transmitter** is an easy and convenient way to provide non-teaching school staff with the ability to call for help from anywhere on the campus. It provides a non-paired alert through any available XD Receiver, alerting the office to the need for some assistance, and using up to five XD Receiver to estimate the location of the individual that activated the SAFE Alert.



XD Duress Button Specifications

Duress Button Controls Alert Reset - Press and Hold
 Alert Switches:
 • Emergency Security Function (SAFE System)– Press and hold both side buttons for 2 seconds to activate

System Frequency	XD Technology 1.9 GHz
Battery Type	Lithium-Ion Battery (rechargeable)
Charge Time	~4 Hours (5V/500mA)
Charging Method	Micro USB charger (supplied)
Temperature Range	41°F - 95°F (5°C ~ +35°C). Maximum Temperature 95°F
Humidity Range	~90%
Weight & Dimensions with Batteries	1.8 oz (50 g) 3.31 (H) x 1.89 (W) x 0.63 (D) in. (84 H x 48 W x 16 D mm)

**The SAFE System (patent pending) is an alert notification system not intended to be a life-saving device or prevent emergencies. Audio Enhancement, our agents, employees, subsidiaries, affiliates and parent companies are exempt from liability for any loss, damage, injury or other consequence arising directly or indirectly from the application of our equipment. In the event of misuse or malfunction of the SAFE System or any of its components, Audio Enhancement, our agents, employees, subsidiaries, affiliates and parent companies are exempt from liability for any loss, damage, injury or other consequence arising directly or indirectly therefrom.*

*Sold only in the USA and Canada



www.AudioEnhancement.com · 800.383.9362