

VIEWpath HEAD END SERVER SPEC SHEET




The **VIEWpath (Video Interactive Education Window)® Head End Server** is a fully integrated audio and video solution that allows educators to record and share lessons, develop as professionals, and record student presentations. Educators are empowered to easily capture and distribute lessons for remote learning along with professional development. Regardless of where a student is, VIEWpath promotes an equitable learning environment in person or virtually.



4 x 3.5 in. Hot Swappable HDD Bays

2 x UBS 3.2 Gen 2 Ports
VGA Display Port

1+1 80 PLUS Gold PSU 1 x RJ 45 ASMB10 iKVM Port



VGA Display Port
COM Port
HDMI Display Port
2 x UBS 3.2 Gen 2 Ports

Power Switch
Q-Code/Port 80 LED

SPECIFICATIONS

VIEWpath HEAD END SERVER	
Processor Support	1 x Socket LGA 1200 Intel® Xeon® E processors (up to 95W) Intel® Pentium™ processors
Core Logic	Intel® C252 PCH
Memory	Total Slots 4 (2 channel) Capacity Maximum up to 128GB Memory Type DDR4 3200/2933/2666 ECC and non ECC UDIMM Memory Size 32GB, 16GB, 8GB, 4GB (UDIMM)
Expansion Slots	Total PCI/PCIx/PCI E/PIKE Slots (3) Slot Type 1 x PCI E x 16 (Gen4 x16 Link, switch to x8 link when slot B occupied), FH/HL 1 x PCI E x 8 (Gen4 x8 Link), HH/HL 1 x PCI E x 8 (Gen3 x4 Link), Proprietary R/A slot (optional for Intel X710 10G LAN card)
Disk Controller	SATA Controller Intel® C252 Chipset 6 x SATA3 6Gb/s ports Intel®VROC (For Linux/ Windows) (Support Software RAID 0/1/5/10) SAS Controller ASUS PIKE II 3008 8i 8 port SAS 12G RAID card ASUS PIKE II 3108 8i 8 port SAS 12G HW RAID card
Storage Bays	4 x 3.5"/2.5" Hot Swap HDD Bays, up to (2*SATA/SAS/ NVMe + 2*SATA/
Networking	2 x Intel® I210 AT + 1 x Mgmt LAN
Graphic	Aspeed AST2600 with 64MB VRAM
I/O Ports	Rear I/O Ports 2 x USB 3.2 Gen 2 ports 1 x VGA port * 1 x HDMI port from CPU 1 x COM port 2 x RJ 45 ports 1 x RJ 45 ports (One for ASMB10 iKVM)(Optional) Front I/O Ports 1 x VGA port* 2 x USB 3.2 Gen1 ports *Must support by ASMB10
Power Supply	Single 350W 80 PLUS Gold PSU (RS300-E11-PS4) 1+1 450W 80 PLUS PLATINUM RPSU (RS300-E11-RS4)

VIEWpath HEAD END SERVER (CONTINUED)	
Switch/LED	Rear Switch/LED: 1 x Q-Code/Port 80 LED 1 x Power switch Front Switch/LED: 1 x Power switch/LED 1x Location switch/LED 1 x Reset switch 1 x HDD Access LED 1 x Message LED LAN 1-2 LED
Environment	Operation temperature: 10°C~ 35°C Non operation temperature: -40°C~ 70°C Non operation humidity: 20% ~ 90% (Non condensing)
Weight	22.70 lbs. (363.32 oz)
Dimensions	1.73 (H) x 17.3 (W) x 19.57 (D) in. (497 x 439.5 x 44 mm)