

XD SOLO®

SPEC SHEET



The **XD Solo®** is a portable speaker system that emits crystal clear audio in any location to meet the needs of today's media-rich learning environments. With built-in Voice Priority, the system will automatically lower the volume of music when a person speaks into a paired XD microphone. Made for maximum portability, this system has built-in rechargeable batteries, an easy-to-carry handle, and a flat base for setting on any surface.



SPECIFICATIONS

XD Solo®	
FREQUENCY Response	70 Hz ~ 18 kHz ± 3 dB
Sensitivity	Input Dependent
Signal to Noise Ratio	>70 dB
Maximum SPL	105 dB
Output Power	150 Watt
Mic/Line Input Connectors	Two XLR/1/4" Combo Mic/Line In, RCA - 1/8" Stereo-Aux Input, SD, & USB
ALD Line Output Connector	1/8" - Aux Output (3.5 mm)
Controls	Master Volume, Low, Mid, High, CH1 Volume, CH2 Volume, Aux In, ALD Level
Wireless Type	DECT
Speaker	8" Woofer, 1" Tweeter
Batteries	12.9 V, 3.35Ah 1 quantity (18650 LiON) Rechargeable Battery
Running Time	8-10 Hours
Charging Time	7-8 Hours
Power Requirements	32 V DC 2A (Universal 100-240 V AC 50/60 Hz Power Supply Included)
Weight	18.85 lbs (8.55 kg)
Dimensions	17.25 (H) x 10.5 (W) x 11.5 (D) in (438 x 267 x 292 mm)
Temperature Range	32° F - 104° F (0° C - 40° C)
Remote control via Microphone	Audio controls: Mic 1, Mic 2
WIRELESS SPECIFICATIONS	
SYSTEM Frequency	DECT 1.9 GHz
Microphone Type	Unidirectional electret condenser microphone
Typical Range of XD Microphone	100 - 120 ft