

# INTERACTIVE TOUCH CONTROLLER

## SPEC SHEET



The **Interactive Touch Controller** is a programmable 3.5" multipurpose wall panel with an interactive display for use with EPIC (Education Paging & Intercom Communications) System®. The ITC is managed via EPIC, allowing for quick adjustments in a classroom to accommodate the ever-changing campus environment. The digital interface allows educators to initiate intercom, link XD Microphones, send SAFE Alerts, and other customizable functions. The ITC2 includes an ambient microphone that supports two-way communications. Educators can send various levels of alerts. During a lockdown, teachers can interact with ITC to inform the administration that they have secured their classrooms.



## SPECIFICATIONS

INTERACTIVE TOUCH CONTROLLER	
Communications	RS-232 control through amp
Mounting	Low voltage mounting bracket or 2-gang wall box
Display	3.5" Full-color touch display
Color	White
Terminations	RJ45 (RS-232 & 24V DC)
Power	24V DC
Weight	0.40 lbs (6.40 oz)
Dimensions	4.50 (H) x 4.50 (W) x 1.25 (D) in. (114.3 x 114.3 x 31.75 mm)

\*To connect the ITC2 ambient microphone to an MS-600 or MS-500 an adapter cable (AC-2179 ) is required.