

IP Speaker Clock

Spec Sheet



The Audio Enhancement® **IP Speaker Clock** combines paging, intercom, synchronized timekeeping, and visual alerts into one IP-based device. Designed for K-12 schools, it improves safety, simplifies communication, and reduces deployment costs.



Specifications

EP-0067 IP Speaker Clock	
Display Type	Full-color HD LCD
Display Resolution	1920 x 720
Display Size	11.69"
Speaker Size	8" High-efficiency speaker
Audio Coverage	Up to 600 ft²
Frequency Response	60 Hz - 17 kHz
Speaker Sensitivity	95 dB @ 1W / 1m
Microphone	Integrated hands-free two-way intercom
Visual Alerting	RGB flashing LED alert bar
Ethernet	10/100/1000 Mbps gigabit ethernet
Network Protocols	SIP, IPv4, IPv6, DHCP, SNMPv1/v2c, HTTP, TCP/IP, UDP, LLDP-MED, IGMP, ICMP, mDNS
Audio Codecs	G.711 A-law, G.711 μ -law
Audio Connections	3.5 mm line input and line output
Power Requirement	PoE+ (IEEE 802.3at)
Maximum Power Consumption	30 W
Cabling	Cat5e or Cat6
Mounting	Wall-mount bracket included
Operating Temperature	14° F to 122° F (-10° C to 50° C)
Humidity	0% – 95% non-condensing
Bracket Load Rating	Single-sided: 100 lbs / double-sided: 200 lbs
Color	Matte Black (EP-0067) Matte White (EP-0068)
Certifications	ISO certified manufacturing
Included Software	ClockWise Campus
Warranty	Standard Audio Enhancement warranty
Dimensions	15.58 (H) × 13.51 (W) × 4.54 (D) in (39.57 x 34.32 x 11.53 cm)
Weight	9.5 lbs (4.3 kg)
Minimum EPIC Version	3.3.0